


MODEL: SBMT-12DG-55



Plane Chart:

Unit:(mm) Terminal type:(T1)




 ISO 9001
 ISO 14001
 OHSAS18001

Parameter Chart:

Volts		12V
Capacity(25°C)	20 hours rate (2.75A)	55Ah
Discharge Current Testing (25°C)	1 hours rate (30.2A)	30.5Ah
	3 hours rate (13.7A)	41Ah
Internal Resistance	Full Charged Battery 25°C	8mΩ
Capacity Affected By Temperature	40°C	104%
	25°C	100%
	0°C	83%
	-15°C	65%
Residual Capacity (25°C)	Capacity After 3 Months Storage	91%
	Capacity After 6 Months Storage	82%
	Capacity After 12 Months Storage	65%
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 16.5A Voltage 14.5~14.9V
	Float (25°C)	Charge Voltage 13.6~13.8V
Weight (Approx)		16.8Kg

Residual Capacity

Discharge Current 25°C


★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.

MODEL: SBMT-12DG-55
Constant voltage charging characteristics

Cycle service life in relation to the depth of discharge

Constant Current Discharge Characteristics (A, 25°C)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	170.4	126.3	97.2	55.2	30.8	20.1	13.8	9.2	6.0	5.5	2.9
10.2V	161.3	120.2	93.2	53.8	29.7	19.8	13.7	9.1	5.9	5.4	2.9
10.5V	159.4	118.3	91.3	52.2	28.5	19.6	13.2	8.9	5.8	5.3	2.8
10.8V	151.6	112.4	88.4	50.2	27.6	19.4	12.6	8.7	5.6	5.3	2.8

Constant Power Discharge Characteristics (Watt, 25°C)

F.V/Time	10min	10min	15min	30min	60min	2h	3h	5h	8h	10h	20h
9.60V	1773.8	1366.8	1065.2	672.4	395.8	222.5	166.3	113.2	74.8	64.7	34.5
10.2V	1679.6	1296.7	1021.1	644.3	379.8	219.5	164.3	112.2	74.1	64.1	34.4
10.5V	1657.5	1279.6	1000.1	630.3	368.4	216.5	162.3	111.2	73.6	64.0	34.4
10.8V	1571.4	1216.5	968.0	610.3	359.7	214.4	160.3	110.2	72.7	63.8	34.3

Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.